

C.C.E.A. model P 770 (see picture 2)

:: technical and electrical features ::	
colors	BLACK
power	9 WATT
glass reflector	PLEXIGLASS
arm type	FLEXIBLE ARM COVERED WITH THERMORETRACTABLE SHEATH FOR PROTECTION AGAINST LIQUIDS AND DUST
arm length	FLEX mm 700
arm diameter	FLEX mm. 15
external dimension of reflector	mm 45 x 180
weight	Kg 1,9
lightbulb	NEON 9 WATT
lightbulb connection	TYPE G 23 FOR 9 WATT
switch	ON FEEDER HOLDER
reflector movement	SWIVEL BY ROTATION OF 360° AND 90° ON AXIS
reflector grade of protection	IP 20
components grade of protection	IP 20
internal lamp cable	RUBBER FAIRLEAD PROTECTED CABLE PASSES THROUGH INSIDE OF LAMP
feeder cable	LENGTH. 1200 mm. mm 23 x 1. PLUG FROM 10 TO 260 V.
transformer	FEEDER 110 AND 230 VOLT
packaging	INDIVIDUAL PER LAMP

:: optical features ::	
type of light	BRIGHT LIGHT
light extension (ray)	DIFFUSED

Application fields: industrial sewing machine, Goldsmith machine manufacturers, work table, machine shop, desk lighting.....

Fixing: see the photo (picture 1) with 4 screws, with metallic clamp for square base (clamp03), with metallic clamp and transformer separated (model TR)





